

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

SECTION 1: Identification

1.1 Product identifier

Trade name **DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)**

Alternative number(s) 212-233, 961-970

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Coating and paint

1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc.
1396 Jefferson Avenue
Dunmore PA 18509
United States

Telephone: +1 (570) 344-1202
Telefax: (570) 969-7634
e-mail: sales@ugl.com
Website: <http://www.ugl.com/>

e-mail (competent person) mark.fortese@ugl.com (Mark Fortese)

1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)
This number is only available during the following office hours: Mon-Fri 08:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.6	carcinogenicity	1A	Carc. 1A	H350

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H350 May cause cancer.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	If exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling Quartz (SiO₂), Distillates (petroleum), hydro-treated heavy paraffinic

2.3 Other hazards

Hazards not otherwise classified

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Titanium dioxide	CAS No 13463-67-7	10 - < 25	Carc. 2 / H351	
Quartz (SiO ₂)	CAS No 14808-60-7	1 - < 5	Carc. 1A / H350	
Aluminium oxide	CAS No 1344-28-1	< 1	Acute Tox. 3 / H331	
Distillates (petroleum), hydro-treated heavy paraffinic	CAS No 64742-54-7	< 1	Acute Tox. 4 / H332 Carc. 1B / H350	
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 1	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317	

For full text of abbreviations: see SECTION 16.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	kaolin	1332-58-7	REL		10 (10 h)						NIOSH REL
US	kaolin	1332-58-7	PEL		15					i, dust	29 CFR 1910.1000
US	kaolin	1332-58-7	REL		5 (10 h)					r	NIOSH REL

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	kaolin	1332-58-7	PEL		5					r, dust	29 CFR 1910.1000
US	kaolin	1332-58-7	PEL (CA)		2					r, noAsb_less1Sil	Cal/ OSHA PEL
US	kaolin	1332-58-7	TLV®		2					r, noAsb_less1Sil	ACGIH® 2019
US	alpha-Alumina	1344-28-1	REL							appx-D	NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15					i, dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r, dust	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	ACGIH® 2019
US	aluminium oxide	1344-28-1	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5					r	Cal/ OSHA PEL
US	titanium dioxide	13463-67-7	TLV®		10						ACGIH® 2019
US	titanium dioxide	13463-67-7	PEL		15					i, dust	29 CFR 1910.1000
US	titanium dioxide	13463-67-7	REL							lowest, appx-A	NIOSH REL
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL

Notation

- appx-A NIOSH Potential Occupational Carcinogen (Appendix A)
- appx-D see Appendix D - Substances with No Established RELS
- Ceiling-C ceiling value is a limit value above which exposure should not occur
- dust as dust
- i inhalable fraction
- lowest exposure by all routes should be carefully controlled to levels as low as possible
- noAsb_less1 contains no asbestos and less than 1% free crystalline silica
- Sil
- r respirable fraction
- STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	DNEL	6.81 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2-benzisothiazol-3(2H)-one	2634-33-5	DNEL	0.966 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	4.03 µg/l	aquatic organisms	freshwater	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	0.403 µg/l	aquatic organisms	marine water	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	1.03 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	49.9 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	4.99 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	3 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	255 °C at 102.4 kPa
Flash point	5,001 °C
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	1.3 Pa at 20 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	388 °C

Viscosity

- Dynamic viscosity	71 mPa s at 25 °C
Explosive properties	none
Oxidizing properties	none

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Aluminium oxide	1344-28-1	inhalation: vapor	3 mg/l/4h
Aluminium oxide	1344-28-1	inhalation: dust/mist	0.888 mg/l/4h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	inhalation: vapor	11 mg/l/4h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	inhalation: dust/mist	2.18 mg/l/4h
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Quartz (SiO ₂)	14808-60-7	1	
Titanium dioxide	13463-67-7	2B	

Legend

- 1 Carcinogenic to humans
2B Possibly carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- 14.1 UN number** not subject to transport regulations
- 14.2 UN proper shipping name** not assigned
- 14.3 Transport hazard class(es)** not assigned
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**
There is no additional information.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
Aluminium oxide	1344-28-1	fibrous forms	1986-12-31

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Titanium dioxide	13463-67-7		IARC Carcinogens - 2B Prop 65
Quartz (SiO ₂)	14808-60-7		IARC Carcinogens - 1
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		EC Annex VI CMRs - Cat. 1B

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO ₂)		1095			1.0 %
Aluminium oxide	1344-28-1				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO ₂)		A, *	
Titanium dioxide	13463-67-7	A	
Titanium dioxide		A	dust

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- dust If the substance poses an airborne particulate exposure hazard, the substance is followed by the word "dust."

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO ₂)	14808-60-7		CA
Titanium dioxide	13463-67-7		
Aluminium oxide	1344-28-1		

Legend

- CA Carcinogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
QUARTZ (SiO ₂)	14808-60-7	
TITANIUM OXIDE (TiO ₂)	13463-67-7	
ALUMINUM OXIDE (Al ₂ O ₃)	1344-28-1	E

Legend

- E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO ₂)	14808-60-7	T
Titanium dioxide	13463-67-7	T
Aluminium oxide	1344-28-1	T

Legend

- T Toxicity (ACGIH®)

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer

VOC content

Regulated Volatile Organic Compounds (VOC-EPA): Regulated Volatile Organic Compounds (VOC-Cal ARB):

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

Abbr.	Descriptions of used abbreviations
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

DRYLOK® Latex Concrete Floor Paint (White/Light Tint Base)

Version number: REV 1.0

Date of compilation: 2020-06-02

End of safety data sheet