



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l 2022**

Alternative number(s) 438xx UFI: 6HAW-P3H8-600J-U1D4

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Floor Paint  
paint related material

#### 1.3 Details of the supplier of the safety data sheet

Sika Corporation  
1396 Jefferson Avenue  
Dunmore PA 18509  
United States

Telephone: +1 (570) 344-1202

Telefax: (570) 969-7634

e-mail:

retailorders@us.sika.com

Website:

http://www.drylok.com/

e-mail (competent person) Crossley.robin@us.sika.com (Robin Crossley)

#### 1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)  
Emergency telephone number: outside office hours

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H317 May cause an allergic skin reaction.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### - Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P321	Specific treatment (see on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to industrial combustion plant.

### - Hazardous ingredients for labelling

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one

## 2.3 Other hazards

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Quartz (SiO <sub>2</sub> )	CAS No 14808-60-7	5 – < 10	Carc. 1A / H350
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 0.05	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS No 55965-84-9	< 0.05	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 4 / H332 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317

For full text of abbreviations: see SECTION 16.

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as frost

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	kaolin	1332-58-7	REL		10 (10 h)					i	NIOSH REL
US	kaolin	1332-58-7	PEL		15					i, dust	29 CFR 1910.1000
US	kaolin	1332-58-7	REL		5 (10 h)					r	NIOSH REL
US	kaolin	1332-58-7	PEL		5					r, dust	29 CFR 1910.1000
US	kaolin	1332-58-7	PEL (CA)		2					r, noAsb_1ess1Sil	Cal/OSHA PEL
US	kaolin	1332-58-7	TLV®		2					r, noAsb_1ess1Sil	ACGIH® 2022
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL

#### Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
i	inhalable fraction
noAsb_less1	contains no asbestos and less than 1% free crystalline silica
Sil	
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
	time-weighted average (unless otherwise specified)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	brown
Particle	not relevant (liquid)
Odor	Amine



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### Other safety parameters

pH (value)	8 – 9.5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	2.3 kPa at 25 °C
Density	0.93 – 1.33 g/cm <sup>3</sup> at 25 °C
Vapor density	this information is not available

### Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	388 °C

### Viscosity

- Kinematic viscosity	751.9 mm <sup>2</sup> /s at 25 °C
- Dynamic viscosity	800 – 1,000 cP at 25 °C
Explosive properties	none
Oxidizing properties	none

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	oral	457 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	dermal	660 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	inhalation: vapor	11 mg/l/4h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	inhalation: dust/mist	2.36 mg/l/4h

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitization

May cause an allergic skin reaction.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Quartz (SiO <sub>2</sub> )	14808-60-7	1	

#### Legend

1 Carcinogenic to humans

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	LC50	16.7 mg/l	fish	96 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	EC50	2.94 mg/l	aquatic invertebrates	48 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	ErC50	150 µg/l	algae	72 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	LC50	0.19 mg/l	fish	96 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	EC50	0.16 mg/l	aquatic invertebrates	48 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	ErC50	19.9 µg/l	algae	72 h





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	EC50	13 mg/l	microorganisms	3 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	LC50	0.07 mg/l	fish	14 d
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	EC50	>0.18 mg/l	aquatic invertebrates	21 d
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	ErC50	45.6 µg/l	algae	120 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### SECTION 14: Transport information

- 14.1 UN number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** not assigned
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Transport in bulk according to IMO instruments**  
The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

##### Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

##### International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

##### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Quartz (SiO2)	14808-60-7		IARC Carcinogens - 1

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO2)		1095			1.0 %

- Hazardous Substances List (MN-ERTK)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

Name of substance	CAS No	References	Remarks
Quartz (SiO <sub>2</sub> )		A, *	

### Legend

\* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO <sub>2</sub> )	14808-60-7		CA

### Legend

CA Carcinogenic

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
QUARTZ (SIO2)	14808-60-7	

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO <sub>2</sub> )	14808-60-7	T

### Legend

T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
1,4-dioxane	123-91-1		cancer
ethylene oxide	75-21-8		cancer
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
acetaldehyde	75-07-0		cancer

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

### Legend

KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l 2022	Trade name: 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l 2022	yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.2	- Signal word: danger	- Signal word: warning	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2	- Hazardous ingredients for labelling: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), methyl-1H-benzimidazol-2-ylcarbamate, 1,2-benzisothiazol-3(2H)-one	- Hazardous ingredients for labelling: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one	yes
2.3	Endocrine disrupting properties: Contains an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$ .		yes
3.2		Description of the mixture: change in the listing (table)	yes
9.1		Kinematic viscosity: 751.9 mm <sup>2</sup> /s at 25 °C	yes
11.1	Germ cell mutagenicity: May cause genetic defects.	Germ cell mutagenicity: Shall not be classified as germ cell mutagenic.	yes
11.1	Reproductive toxicity: May damage the unborn child. May damage fertility.	Reproductive toxicity: Shall not be classified as a reproductive toxicant.	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.6	Endocrine disrupting properties: Contains an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$ .	Endocrine disrupting properties: None of the ingredients are listed.	yes



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## 438xx)DRYLOK® Latex Concrete Floor Paint - (Dark Tint Base) <50g/l

Version number: REV 2.0  
Replaces version of: 2022-10-11 (REV 1)

Revision: 2022-10-19

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1	Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)		yes
15.1	List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)		yes
15.1		List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4): change in the listing (table)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H350	May cause cancer.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

### End of safety data sheet