

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **DRYLOK® Masonry Crack Filler (Master)**  
 Alternative number(s) 30507; UFI: M6WH-AS96-780W-AW9G

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use

#### 1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc. - Sika  
 1396 Jefferson Avenue  
 Dunmore PA 18509  
 United States

Telephone: +1 (570) 344-1202  
 Telefax: (570) 969-7634  
 e-mail: sales@ugl.com  
 Website: <http://www.ugl.com/>

e-mail (competent person) Robin.Crossley@ugl.com (Robin Crossley)

#### 1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)  
 Emergency telephone number: outside office hours

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.6	carcinogenicity	1A	Carc. 1A	H350

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H350 May cause cancer.

**DRYLOK® Masonry Crack Filler (Master)**

Version number: REV 1.0

Date of compilation: 2024-06-07

**- Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	If exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

**- Hazardous ingredients for labelling** Quartz (SiO<sub>2</sub>)**2.3 Other hazards**

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Contains an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not relevant (mixture)

**3.2 Mixtures**

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	1 - < 5	Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Quartz (SiO <sub>2</sub> )	CAS No 14808-60-7	0.05 - < 1	Carc. 1A / H350
Pentapotassium triphosphate	CAS No 13845-36-8	0.05 - < 1	Acute Tox. 2 / H330

**Remarks**

For full text of abbreviations: see SECTION 16

**SECTION 4: First-aid measures****4.1 Description of first-aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

**DRYLOK® Masonry Crack Filler (Master)**

Version number: REV 1.0

Date of compilation: 2024-06-07

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Fire-fighting measures****5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

**5.2 Special hazards arising from the substance or mixture**

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

**6.3 Methods and material for containment and cleaning up**

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

frost

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	calcium carbonate	1317-65-3	PEL		15					dust	29 CFR 1910.1000
US	calcium carbonate	1317-65-3	REL		10 (10 h)					natural	NIOSH REL
US	calcium carbonate	1317-65-3	PEL		5					r	29 CFR 1910.1000
US	calcium carbonate	1317-65-3	REL		5 (10 h)					r, natural	NIOSH REL
US	limestone	1317-65-3	REL		10 (10 h)						NIOSH REL
US	limestone	1317-65-3	REL		5 (10 h)					r	NIOSH REL
US	quartz	14808-60-7	PEL (CA)		0.05					r, dust	Ca/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.098					eq1a, r, dust	29 CFR 1910.1000

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	silica, crystalline - quartz	14808-60-7	PEL		0.294					eq2a, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	PEL	84.05						eq-ph1a, partml, r, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	TLV®		0.025					r	ACGIH® 2024
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, dust, appx-A	NIOSH REL

**Notation**

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
eq-ph1a	$mppcf = 250 / (\%SiO_2 + 5)$
eq1a	$mg/m^3 = 10 / (\%SiO_2 + 2)$
eq2a	$mg/m^3 = 30 / (\%SiO_2 + 2)$
natural	natural
partml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
	time-weighted average (unless otherwise specified)

### 8.2 Exposure controls

**Appropriate engineering controls**

General ventilation.

**Individual protection measures (personal protective equipment)**

**Eye/face protection**

Wear eye/face protection.

**Skin protection**

**- Hand protection**

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**- Other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

##### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

##### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

**DRYLOK® Masonry Crack Filler (Master)**

Version number: REV 1.0

Date of compilation: 2024-06-07

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

No known hazardous reactions.

**10.4 Conditions to avoid**

There are no specific conditions known which have to be avoided.

**10.5 Incompatible materials**

Oxidizers

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

## Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

## Acute toxicity

Shall not be classified as acutely toxic.

## Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Pentapotassium triphosphate	13845-36-8	inhalation: dust/mist	>0.39 mg <sub>i</sub> /4h

## Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

## Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

## Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

May cause cancer.

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Quartz (SiO <sub>2</sub> )	14808-60-7	1	

#### Legend

1 Carcinogenic to humans

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
Pentapotassium triphosphate	13845-36-8	LC50	1,850 mg/l	fish	24 h
Pentapotassium triphosphate	13845-36-8	EC50	>100 mg/l	aquatic invertebrates	48 h

#### Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
Pentapotassium triphosphate	13845-36-8	ErC50	>900 mg/l	algae	7 d
Pentapotassium triphosphate	13845-36-8	EC50	>1,000 mg/l	microorganisms	3 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.



**DRYLOK® Masonry Crack Filler (Master)**

Version number: REV 1.0

Date of compilation: 2024-06-07

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .**12.6 Endocrine disrupting properties**Contains an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information**

<b>14.1 UN number</b>	not subject to transport regulations
<b>14.2 UN proper shipping name</b>	not relevant
<b>14.3 Transport hazard class(es)</b>	none
<b>14.4 Packing group</b>	not assigned
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	There is no additional information.
<b>14.7 Transport in bulk according to IMO instruments</b>	The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations****Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Not subject to transport regulations.

**International Maritime Dangerous Goods Code (IMDG) - Additional information**

Not subject to IMDG.

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Not subject to ICAO-IATA.

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from listing

##### Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

##### Clean Air Act

none of the ingredients are listed

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Quartz (SiO <sub>2</sub> )	14808-60-7		IARC Carcinogens - 1

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO <sub>2</sub> )		1095			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO <sub>2</sub> )		A, *	

##### Legend

\* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO <sub>2</sub> )	14808-60-7		CA

##### Legend

CA Carcinogenic

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO <sub>2</sub> )	14808-60-7	T
Quartz (SiO <sub>2</sub> )	14808-60-7	T

##### Legend

T Toxicity (ACGIH®)

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer
carbon black	1333-86-4	airborne, unbound particles of respirable size	cancer
talc	14807-96-6	containing asbestiform fibers	cancer
ethylene glycol (ethanediol)	107-21-1		developmental
1,4-dioxane	123-91-1		cancer

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

## DRYLOK® Masonry Crack Filler (Master)

Version number: REV 1.0

Date of compilation: 2024-06-07

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
VN	NCI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

## Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

## Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**DRYLOK® Masonry Crack Filler (Master)**

Version number: REV 1.0

Date of compilation: 2024-06-07

**List of relevant phrases (code and full text as stated in section 2 and 3)**

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H330	Fatal if inhaled.
H350	May cause cancer.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

**End of safety data sheet**