



COVERAGE

48 Linear ft. per 1/4" bead



CURE TIME

12 Hours



CLEAN-UP

Soap and water

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

PRODUCT DATA SHEET

Publication Date: 9-30-20

DRYLOK® Masonry Crack Filler

PRODUCT DESCRIPTION

DRYLOK® Masonry Crack Filler is formulated to seal and waterproof cracks in interior and exterior concrete walls, walkways, steps, driveways, garage and basement floors, and to replace cracked mortar joints. Dries to the color of concrete. Will not bleed. Reduces radon gas penetration. Fast easy clean up with water. Easy gunning with excellent adhesion, even to damp surfaces. May be painted over after one hour with latex paint.

- Siliconized acrylic latex creates a flexible bond
- Seals and waterproofs cracks in concrete and masonry
- Replaces cracked mortar joints
- Excellent adhesion even to damp surfaces
- Reduces radon gas penetration
- Fills horizontal and vertical cracks

BASIC USES

The product seals and waterproofs interior and exterior cracks in concrete walks, steps, floors, and replaces cracked mortar joints.

TECHNICAL DATA

COMPOSITION: Acrylic fortified with silicone

SHEEN: N/A

% WEIGHT SOLIDS: 83%

DENSITY (LBS./US GAL.): 13.4

VISCOSITY: N/A

pH: 7.5

COLORS:

- Gray

DRYLOK® MASONRY CRACK FILLER

CURE TIME: 12 hours

- May be subjected to traffic in 2 hours
- Paintable in 1 hour with latex paint
- Allow overnight before painting with oil base paint

Do not apply in extreme dampness or high humidity.

Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

COVERAGE:

48 Linear ft. per 1/4" bead

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

RECOMMENDED FILM THICKNESS/COAT: N/A

FLASH POINT: N/A

SHELF LIFE: 3 Years unopened container

FREEZE/THAW: Protect from freezing

CONTAINER SIZES: Ten and one-half fluid ounces (US) caulk tube

VOC

57 g/L

TINTING

N/A

LIMITATIONS

Do not store in areas of extreme heat or cold. Not to be used as a substitute for high temperature furnace cement or fireplace mortar. Not recommended for use under water in concrete pools, fish ponds, etc.

SURFACE PREPARATION

Opening to be sealed must be free from frost, dust, dirt, oil, and loose particles. Hosing and wire brushing facilitate cleaning.

APPLICATION

Apply only when air and surface temperatures are above 50°F (10°C). Crack must be free from frost, dust, dirt, oil, and loose particles. Wire brushing and hosing facilitates cleaning. Remove excess moisture. Place in

any standard caulk gun. Cut end of plastic spout at 45° angle to desired opening size. Force sealant tightly into crack. Use only in cracks 1/2" (12mm) wide or less. Deep cracks over 1/4" (6mm) should be filled with backing material to within 1/4" (6mm) of surface before filling with DRYLOK® Masonry Crack Filler. Smooth patch with wet putty knife or trowel.

CAUTION

AVOID EYE CONTACT. MAY CAUSE EYE IRRITATION. DO NOT INGEST.

KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

If spilled, contain spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulators.

FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠ Warning: Cancer and Reproductive Harm
www.P65Warnings.ca.gov.


DRYLOK® MASONRY CRACK FILLER

For additional health and safety information, please refer to the Safety Data Sheet (SDS).

DRYLOK® is a registered trademark of United Gilsonite Laboratories (UGL).

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

	CONTAINER	NUMBER/CASE	COLOR	ORDER NUMBER
DRYLOK® Masonry Crack Filler	10.5 fl. ounce	10/case	Gray	30507



Gray

Note: Color swatches are representative only.



1-800-845-5227 • Fax 1-570-969-7634 • www.UGL.com

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509

Mail to: P.O. Box 70, Scranton, PA 18501-0070

Plant Locations: Jacksonville, IL • Jackson, MS