



COVERAGE

2 oz.–4 oz./gal.



DRY TIME

Varies on Usage



CLEAN-UP

Vacuum clean spillage. If sweeping, use a dust suppressant.

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

PRODUCT DATA SHEET

Publication Date: 8-31-20

DRYLOK® Non-Skid Texture Additive

PRODUCT DESCRIPTION

DRYLOK® Non-Skid Texture Additive increases traction and helps prevent slipping and falling by providing a slip resistant coating. For use with DRYLOK® E1 Latex 1-Part Epoxy Concrete Floor Paint and other oil, latex, or epoxy floor paints. DRYLOK® Non-Skid Texture Additive will not change the drying characteristics or film thickness recommendation of the paint that it is added to. It will however alter the appearance of the surface by lowering the gloss due to the light scattering effect of the particles that will stick up out of the surface of the paint. DRYLOK® Non-Skid Texture Additive contains natural pumice.

- Lightweight aggregate additive to paint, does not settle to bottom
- Increase traction and help prevent falls, accidents and injuries

BASIC USES

Use on garage floors, patios, stairs, basements, driveways, ramps and walkways.

TECHNICAL DATA

COMPOSITION: powder

SHEEN: N/A

% WEIGHT SOLIDS: 100%

% VOLUME SOLIDS: 100%

DENSITY (LBS./US GAL.): 19.6 ± 0.1

VISCOSITY: N/A

pH: N/A

COLORS:

- off white

DRY TIME: N/A

COVERAGE:

2 oz.–4 oz./gal.

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

DRYLOK® NON-SKID TEXTURE ADDITIVE

RECOMMENDED FILM THICKNESS/COAT:

N/A

SHELF LIFE: N/A

Freeze/Thaw: N/A

CONTAINER SIZES: 4 ounce (US) container

VOC

N/A

SURFACE PREPARATION

Add 4 oz. bottle to 1 gallon of any oil, latex based or epoxy floor paint. Pour powder into paint and mix thoroughly. For best results use a drill with a stirring blade. Stir thoroughly before and during application.

APPLICATION

N/A

SPECIFICATION

N/A

CAUTION

Wear eye goggles to prevent eye irritation.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

EYES: Flush with copious amounts of clean water for 15 minutes. Consult a physician if irritation persists.

SKIN: None known.

INGESTION: Non-Hazardous

INHALATION: Blow nose, rinse mouth, drink water to clear throat. Move to fresh air

For additional health and safety information please refer to the "Safety Data Sheet".

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional health and safety information, please refer to the "Materials Data Sheet".

DRYLOK® is a registered trademark of United Gilsonite Laboratories (UGL).

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

	CONTAINER	NUMBER/CASE	ORDER NUMBER
DRYLOK® Non-Skid Texture Additive	4 OZ.	6/case	01804



1-800-845-5227 • Fax 1-570-969-7634 • www.UGL.com

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509
Mail to: P.O. Box 70, Scranton, PA 18501-0070
Plant Locations: Jacksonville, IL • Jackson, MS