

## DRYLOK® PRO MASONRY WATERPROOFER SPRAY SPECIFICATION FOR LOWE'S

Utilizing a Graco Max II 595 PC Pro Electric Airless Sprayer, Hi-Boy

- ¼" X 50' HOSE
- MAX GPM 0.7
- MAXIMUM TIP SIZE 0.027
- 30 MESH MANIFOLD FILTER
- 60 MESH GUN FILTER

To achieve production rates at 17 wet mils – best results using a 525 or 527 reversible tip. (Two passes overlapping the spray pattern)

If a smaller unit is used such as a Graco 395 or Titan 440i (0.54 GPM) maximum tip size is a 0.23 tip – Several passes (3-4) are needed to achieve the 17 wet mils

The smaller the tip size, .017-.019-.021 the more chance of tip clogging

Hose size 100' of ¼" ID - The units can handle up to 300' although we suggest 3/8" ID for the first 150ft -drop down to 150' of ¼"

Flush pump and clean sprayer with hot soapy water



### CORPORATE HEADQUARTERS

800-845-5227  
1396 Jefferson Avenue, Dunmore, PA 18509  
Mail to: P.O. Box 70, Scranton, PA 18501-0070

### PLANT LOCATIONS

Dunmore, PA | Jacksonville, IL | Jackson, MS